



VITCON 211 TILE FIX

Multipurpose Polymeric Tile Adhesive

DESCRIPTION

VITCON 211 TILE FIX is a cementitious base powder specially formulated for adhesion of ceramic tiles and marble cladding to building surfaces. **VITCON 211 TILE FIX** is comprised of selected grades of Portland cement admixed with synthetic polymeric additives to suit various requirements of thick/thin bed performance.

ADVANTAGES

- ✓ Easy application.
- ✓ Slow setting property helps the mason to adjust and align the tiles or cladding to achieve a perfect finish.
- ✓ Makes the surface watertight beneath the tiles – best use for swimming pools, bathrooms, toilets and underground structures.
- ✓ Low shrinkage helps better bonding with the surface.

COVERAGE

VITCON 211 TILE FIX mixed with water normally gives coverage of 40 - 45 square feet for a bed thickness of 3 mm. The coverage also depends upon the substrate condition and application procedure.



APPLICATION

1. Addition of water in powder at the ratio of approximately 1:2 or 1:3 by weight depending upon the requirement in consistency for different applications.
2. Gently stir the mix with trowel until a uniform thick consistency is achieved.
3. Apply the mix directly to the surface and press the tile firmly over it. The process can be alternated with applying the mix to the back of the tile and pressing it on the surface. Tiles used should be pre-soaked in water. A 3mm thickness between tile and the surface is recommended for better performance.
4. Remove the surplus mixture from the tiles with a damp cloth. We recommend leaving the tiles for 24hrs after fixing before filling the joints with VITCON 212 TILE JF or equivalent material.

SPECIFICATIONS

Appearance	: Light Grey powder
Storage	: Away from direct sunlight.
Shelf life	: 12 months.

PACKAGING

VITCON 211 TILE FIX is available in 25 kg bag.

SAFETY

VITCON 211 TILE FIX is non-toxic, non-flammable and non hazardous. However, any splash on the human body should be washed out immediately with plenty of water.