



VITCON 212 TILE JF

Tile Joint Filler

DESCRIPTION

VITCON 212 TILE JF is a polymer based cementitious powder specially formulated for filling joints after placing of ceramic tiles and marble cladding to building surfaces. **VITCON 212 TILE JF** is specially formulated with synthetic polymeric additives to get excellent bonding to any building substrate and to reduce permeability to a large extent.

ADVANTAGES

- ✓ Easy to apply on surfaces.
- ✓ Excellent adhesion to both masonry and ceramic substrates.
- ✓ Water resistant suitable to use in swimming pools, bathrooms, toilets and underground structures.
- ✓ Non-shrink property reduces any surface crack.
- ✓ Availability in various colours helps in making aesthetic finish.

COVERAGE

1 kg of **VITCON 212 TILE JF** is used to fill or grout an area of 5 - 6 square meter of tiled surface for a joint width of 3 mm. The consumption may vary depending upon size and width of tiles.



APPLICATION

1. One part of is to mixed 3 to 3.5 parts of water by weight to form a smooth thick paste, depending upon the applications areas.
2. The joints should be made clean, dry and free from any loose particle.
3. Apply the paste directly to the joint either with a sponge, cloth or spatula.
4. Press the joints firmly to ensure that the joints have been properly filled.
5. Remove excess material with a wet cloth.
6. Cure the filled joints with slow pouring of water or damp cloth.
7. Leave the tiles for 24hrs before actual uses.

SPECIFICATIONS

Appearance	: Powder
Pot Life	: Approximately 20 - 25 minutes depending upon ambient temp.
Storage	: Away from direct sunlight.
Shelf life	: 12 months.

PACKAGING

VITCON 212 TILE JF is available in 5 kg / 25 kg bag.

SAFETY

VITCON 212 TILE JF is cementitious powder; hence non-toxic, non-flammable and non hazardous. However, any splash on the human body should be washed out immediately with plenty of water.